

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number
WO 2005/040537 A1

(51) International Patent Classification⁷: **E06B 3/54**

(21) International Application Number:
PCT/GB2004/004370

(22) International Filing Date: 15 October 2004 (15.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0324334.2 17 October 2003 (17.10.2003) GB

(71) Applicant (for all designated States except US): **PILKINGTON PLC** [GB/GB]; Prescot Road, St. Helens, Merseyside WA10 3TT (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WARD, Peter** [GB/GB]; 2 Argyll Close, Garswood, Nr Wigan, Lancashire WN4 0ST (GB). **ROWLAND, Eric** [GB/GB]; 8 Old Mill Hill, Ormskirk, Lancashire L39 4JJ (GB).

BRUNT, William, Henry [GB/GB]; 99 Jean Avenue, Leigh, Lancashire WN7 3LX (GB).


(74) Agents: **HALLIWELL, Anthony, Charles et al.**; Group Intellectual Property Department, Pilkington European Technical Centre, Pilkington, Hall Lane, Lathom, Ormskirk, Lancashire L40 5UF (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: **LOAD BEARING LAMINATES**



(57) Abstract: Laminates comprising at least two glass plys surrounding at least one interlayer having at least one bore extending through the laminate are produced by excluding the interlayer from the area surrounding the bore(s) and positioning a load bearing insert around the bore. The insert may be positioned before or after the laminating process. The invention reduces the tendency for delamination around the area of the bore when the laminate is placed under load.

WO 2005/040537 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.